

GPIB Coaxial Switch

Features

- Four way power (24VDC) output individually.
- Safety of power output
- SPDT and SPMT for option
- GPIB interface control

Application

- 220mm x 189mm x 100mm
- Weight: 1.0 Kg



Specification

Driving power :

Voltage	24 VDC								
Voltage Accuracy	± 1.0%								
Current(one channel)	900 mA								
Protection	Short circuit / Over Voltage								
Output Connector	D-sub 9 Pin (Male)								
Pins	1	2	3	4	5	6	7	8	9
	S1	S2	S4	--	--	GND	S3	--	--

SPDT :

Frequency Range	DC-6 GHz	6-12 GHz	12-18 GHz
V.S.W.R. (Maximum)	1.25 : 1	1.40 : 1	1.50 : 1
Insertion Loss (Maximum)	0.2 dB	0.4 dB	0.5 dB
Isolation (Maximum)	70 dB	60 dB	60 dB
Switching time	20 ms		

SPMT :

Frequency Range	DC-6 GHz	6-12 GHz	12-18 GHz
V.S.W.R. (Maximum)	1.25 : 1	1.40 : 1	1.70 : 1
Insertion Loss (Maximum)	0.2 dB	0.4 dB	0.5 dB
Isolation (Maximum)	70 dB	60 dB	60 dB
Switching time	20 ms		