

SHB-D20 Pneumatic Press Shielding Box

Application

- Excellent electromagnetic shielding and solder float (Excluding Filter connections).
- It's widely used for Bluetooth, GSM, WCDMA, RFID, WLAN, Motorcycle and Mobile, and wireless shielding box system etc.
- In operational application range, several portable test station workable, and don't need any wire connection. The source signal from satellite, don't need to buy any simulations.
- For RF auto testing solution.



Features

- Dimension : 200 x 200 x 195mm
- Small Module or Sip product (PCIe mini, Mini PCI card)
- Weight: 7 kg
- Pneumatic operation
- Additional filters
- For Auto Test machine(XYZ table or robot)
- Optional Accessories:
Card Bus Reader
Card Bus to Mini PCI Adapter
Card Bus to PCI Adapter
Card Bus to Card Bus Adapter
PCIe mini extend card

Specification

Shielding effective	>60dB (2.4GHz and 5.8GHz)	Power	AC110~240V
Fixture air connector	4mm OD hose	SMA connector	SMA*3
Outline dimension(WDH)	200 x 200 x 195mm	Box air connector	6mm OD hose
Inner dimension(WDH)	178 x 178 x 160mm	Structure	Aluminum base
Box color	white		

For more technical information, please contact us by:
TEL: +886-2-26947700 FAX: +886-2-26949821 Email: sales@vicommtech.com