

SHB-V30 Pneumatic Press Shielding Box

Application

- Vicomm SHB-V30 Mobile test shielding Box is a pneumatic control RF test fixture that Provides RF isolation and reliable signal connections Necessary for testing various types of mobile test Devices in a test system.
- With the extensive list of standard accessories, SHB-V30 offers an excellent value for The test needs of production line, R&D, service and QA.



Features

- Dimension : 325 x 233 x 270mm
- High RF Shielding
- Weight: 12 kg
- Pneumatic operation
- Customizable data connections
- EMI filters on all data and DC lines
- Additional filters
- Optional Accessories:
 - Card Bus Reader
 - Card Bus to Mini PCI Adapter
 - Card Bus to PCI Adapter
 - Card Bus to Card Bus Adapter
 - PCIe mini extend card

Specification

Shielding effective	>65dB (2.4GHz and 5.8GHz)	Power	AC110~220V
Fixture air connector	4mm OD hose	SMA connector	SMA*2
Outline dimension(WDH)	345 x 242 x 266.5mm (Close) 345 x 242 x 416.5mm (Open)	Box air connector	6mm OD hose
Inner dimension(WDH)	254 x 155 x 100mm	Structure	Aluminum base
Box color	Brown		

For more technical information, please contact us by:
TEL: +886-2-26947700 FAX: +886-2-26949821 Email: sales@vicommtech.com