

Application

- Switch as a test system or signal processing, signal routing, and played the role of the switching signal transmission path

Feature

- Low Insertion Loss and high Isolation

Specification

- 1 to 2 Coaxial Switch DC-18 GHz



| | | | |
|--------------------------------------|--------------------|------|-------|
| Frequency Rang (GHz) | DC-6 | 6-12 | 12-18 |
| VSWR (:1) max. | 1.25 | 1.40 | 1.50 |
| Insertion Loss (dB) max. | 0.2 | 0.4 | 0.5 |
| Isolation (dB) min. | 70 | 60 | 60 |
| Actuator Operating Voltage (VDC) | 24 | | |
| Actuator Operating Current (mA) max. | 180 @ 24VDC & 20°C | | |
| Switching Time (ms) | 20 | | |

- 1 to 4 Coaxial Switch DC-18 GHz



| | | | |
|----------------------------------|--------------------|------|-------|
| Frequency Rang (GHz) | DC-6 | 6-12 | 12-18 |
| VSWR (:1) max. | 1.25 | 1.40 | 1.70 |
| Insertion Loss (dB) max. | 0.2 | 0.4 | 0.5 |
| Isolation (dB) min. | 70 | 60 | 60 |
| Actuator Operating Voltage (VDC) | 24 | | |
| Actuator Operating Current (mA) | 270 @ 24VDC & 20°C | | |
| Switching Time (ms) | 20 | | |
| Operating Temperature Rang (°C) | -25 - 65 | | |